

# BEEKs™ Asset Beacons

## BLE beacons for asset location services, wayfinding or retail applications

BEEKs™ Bluetooth Low-Energy (BLE) beacons are among the most advanced beacons in the industry. Being fully Apple iBeacon and Google Eddystone compatible, BEEKs beacons may be used for any standard beacon application that provides location based promotional or way-finding services to smartphone users.



When combined with HID Global's end-to-end IoT Services ecosystem, that includes BluFi™ BLE to WiFi gateways and the Bluzone™ cloud services, BEEKs can be centrally managed through the cloud and BluFi devices to transfer new messages, firmware updates and battery status checks remotely. Their unique design allows BEEKs to broadcast reliably even in densely populated WiFi environments.

BEEKs asset beacons are intended for real time location (RTLS) of assets via Bluzone Cloud or retail- / way-finding applications. Software development kits (SDK) for iPhone or

Android allow building Smartphone APPs that react on beacon presence e.g. to show location or route on a map.

HID Global Location Services is an efficient real-time asset location (RTLS) platform leveraging BEEKs beacons to effectively pin down the locations of assets inside a warehouse, campus or manufacturing hall. Beacon location is determined by Bluzone through HID BluFi devices and/or Aruba BLE enabled access points.

BEEKs beacons are available in multiple form factors and sensor configurations for different applications like in form of badges for Workplace optimization or with sensors for condition monitoring of motorized equipment. Their extensible architecture allows organizations to scale deployment of standard beacon applications and extend to centralized management, real-time condition monitoring or location services in a later phase.



### KEY BENEFITS:

- Flexible – Simultaneously supports iBeacon, Eddystone and sBeacon protocol for optimal application compatibility\*
- Multi-Purpose – Used as promotional beacons, for way-finding or asset location\*\*
- Rapid Implementation – Easy to apply anywhere with multi-year battery life.

### TECHNOLOGY HIGHLIGHTS:

- Bluetooth low energy beacons
- iBeacon (Apple), Eddystone (Google) and sBeacon (HID) supported simultaneously
- Location precision down to 6 ft (2 m)
- Central management possible
- Fast and easy roll-out, equipment agnostic
- Optionally support Location Services through Aruba BLE enabled access-points

\*BEEKs mini supports sBeacon protocol only.

\*\*BEEKs mini used for Asset Location only.

\*\*\*Way-finding and Retail advertisement use cases do not apply to the BEEKs Mini.

# BEEKs™ Asset Beacons



## APPLICATION AREAS:

### Real-time location for assets (requires Bluzone™ cloud)

- Indoor position tracking of assets (Tools, portable equipment, vehicles)
- Position based alerting, heat-maps etc.

### Way-Finding Applications\*\*\*

- BEEKs Beacons may be installed in well-known places in buildings, campuses or tunnels
- Specifically designed mobile device APPs can detect the beacons for real-time indoor positioning of the phone
- Can support location and way-finding

### Retail advertisement

- BEEKs beacons may be used in iBeacon and/or Eddystone mode for advertising messages or location based services
- Quick and efficient counting of people at mustering points in emergency situations
- Central provisioning or monitoring via BluFi and Bluzone optionally possible



hidglobal.com

North America: +1 512 776 9000 | Toll Free: 1 800 237 7769

Europe, Middle East, Africa: +44 1440 714 850

Asia Pacific: +852 3160 9800 | Latin America: +52 (55) 9171-1108

For more global phone numbers click here

© 2021 HID Global Corporation/ASSA ABLOY AB. All rights reserved.

2021-11-05-ldt-iots-beeks-asset-beacon-ds-en

PLT-03811

Part of ASSA ABLOY

	BEEKs™ Lite	BEEKs™ Plus	BEEKs™ Mini Asset Tag	BEEKs™ Mini Eyelet
<b>Model Number</b>	BEEKS001	BEEKS001	EMBC20	
<b>Configuration Types</b>	BEEKS001-Lite Asset location and way-finding. VHB tape-mount.	BEEKS001-Plus Asset location and way-finding with longer battery life. VHB tape-mount	EMBC20 - Small beacon for asset real-time location	Accessory for BEEKs Mini to affix via cable-tie - delivered without Beacon
<b>Part Number</b>	BVBLN5W	BVPL09W	BVBMN3B-EM20	BVBMN3B-EYELET
<b>RF SPECIFICATIONS</b>				
<b>Bluetooth standard/ Protocol</b>	Bluetooth Low Energy (BLE) 4.2		Bluetooth Low Energy 5.0	
<b>Frequency Band</b>	2400-2483.5 MHz			
<b>Max Output power</b>	-5.6 dBm e.i.r.p		-1.4 dBm e.i.r.p	
<b>Number of channels</b>	40			
<b>Modulation</b>	GFSK			
<b>Antenna/gain</b>	integral PCB antenna, 0dBi			
<b>Mode of operation</b>	Half duplex			
<b>FEATURES</b>				
<b>BLE Application Supported</b>	Eddystone, iBeacon, sBeacon			
<b>Processor type</b>	ARM Cortex M3 and M0		ARC® EM4	
<b>Memory</b>	55KB Flash		128KB FLASH	
<b>PHYSICAL</b>				
<b>Length x Width</b>	2.36 in x 0.83 x 0.98 in (60 x 21 x 25 mm)	2.41 x 1.46 in (61.3 x 37.2 mm)	1.2 in x 0.4 in (30 x 10 mm)	1.5 in x 0.2 in (38.3 x 5.25 mm)
<b>Mounting Method</b>	3M VHB adhesive sticker		3M VHB adhesive sticker Alternative : Plastic Eyelet	Chip
<b>Housing Material</b>	Polycarbonate and ABS			Plastic
<b>Color</b>	White			Blue
<b>Weight</b>	1 oz (28 g)	2.7 oz (76 g)	0.24 oz (7 g)	
<b>BATTERY</b>				
<b>Type</b>	3.6V / 2600 mAh	3.6V / 7200 mAh	CR-2032 - 3V	
<b>Lifetime (depending on utilization)</b>	Up to 5 years	Up to 8 years	Up to 2 years -1.4 dBm every 4 sec.)	
<b>CHEMICAL AND MECHANICAL RESISTANCE</b>				
<b>Water</b>	IP65	IP65	IP64	
<b>Withstands Exposure To</b>	Water and UV resistant			
<b>THERMAL</b>				
<b>Storage</b>	-13° to +170° F (-25° to +77° C)		-4° to +140° F (-20° to +60° C)	
<b>Operating Temperature</b>	-13° to +170° F (-25° to +77° C)		-4° to +140° F (-20° to +60° C)	
<b>OTHER</b>				
<b>Standards</b>	FCC / CE / JRF / IC	FCC / CE	FCC	
<b>Options</b>	Sensors: See BEEKs Industrial		Plastic Eyelet housing: BVBMN3B-EYELET to affix the beacon with a cable tie	
<b>Box Size</b>	10 pcs.			100 pcs.
<b>Warranty</b>	1 year			

For more information, contact [iotsales@hidglobal.com](mailto:iotsales@hidglobal.com)

